



Wyse 5050 all-in-one PCoIP zero client for VMware

Elegant, secure, and powerful all-in-one zero client that is purpose-built for your VMware environment



Elegantly powerful.

The 5050 is the all-in-one version of our Wyse 5030 PCoIP zero client for VMware. Living inside a Dell P24 monitor (23.6" display), the 5050 combines the security and performance of the Wyse 5030 zero client with the elegant design of Dell's best-selling monitors. With the highest resolution in its class, its dedicated hardware PCoIP engine delivers the highest level of display performance available for advanced applications, including CAD, 3D solids modeling, video editing and more.

Elegant and productive, the Wyse 5050 PCoIP all-in-one zero client is a customer facing VMware View end point that delivers a true PC-like experience with support for dual displays. The Wyse 5050 offers the full benefits of an efficient and secure centralized computing environment, like multiple display support, multimedia playback, HD audio and six USB peripheral ports.

Manageability and security made easy.

The Wyse 5050 PCoIP zero client is easy to provision and manage in the data center and at the desk. This AIO allows you to securely manage your virtual desktops centrally in a data center. Time to productivity couldn't be easier with the 5050, as the device requires just a single power cable and an Ethernet cable to set it up.

With Wyse thin clients, customers get a complete services portfolio including Deployment Services, ProSupport and Accidental Damage service, giving Dell business partners end-to-end support throughout the product lifecycle.

Cool, quiet performance

The 5050 PCoIP all-in-one zero client for VMware draws under 25 watts of power, creating cooler, quieter working environments. Wyse zero clients for VMware receive and decode signals from the PCoIP host to create standard PC interfaces for the display, USB peripherals and audio.



Specifications

Wyse 5050 AIO PCoIP zero client for VMware

Processor	Teradici TERA2321 PCoIP
Memory	512MB RAM DDR3
Power	Internal power supply Worldwide auto-sensing 100–240 VAC, 50/60Hz power supply, Multifunction power button and LED
Power consumption	Less than 25 watts
Security	Built-in Kensington security slot (cable sold separately)
Certifications (Based on US ratings)	VMware Ready, PCoIP Connected
I/O peripheral support	1 DVI-I port , 1 VGA (PC mode) 6 External USB 2.0 ports (4 side, 2 back)
Networking	10/100/1000 Base-T Gigabit Ethernet
Display	23.6" screen size One display: 1920 x 1080 @60Hz, Color Depth: 8, 15, 16 or 24bpp Two displays: 1920 x 1080 @60Hz, Color Depth: 8, 15, 16 or 24bpp Contrast ratio: > 2000:1 View Angle: 160° / 160° (CR _≥ 10)
Audio	Input: Audio 1/8-inch mini jack, Stereo Microphone/Line in Output: 1/8-inch mini jack, full 16-bit stereo, 48KHz sample rate
Dimensions	Height x Width x Depth 339.6 mm x 556.77 mm x 116 mm (13.37 x 21.92 x 59.182 in) Weight 4.3 kg without stand, 6.5 kg with stand
Mountings	Base detachable, Tilt (Yes / -5° (forward) ~15° (backward)), Swivel (90°), Height (120mm), Pivot
Temperature range	Horizontal position 10° to 40° C (50° to 104° F) Vertical position, power button up 10° to 40° C (50° to 104° F) Storage -10° to 60° C (14° to 140° F)
Humidity	Condensing 20% to 80% Non-condensing 10% to 95%
Keyboard and mouse	Enhanced USB keyboard with Windows Keys (104 keys) USB mouse (availability varies by region).
Warranty	3-year limited hardware warranty
Support and deployment	Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service.

Learn more: Visit www.dell.com/wyse

Dell Inc.
One Dell Way
Round Rock, TX 78664

Visit our website at:
www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
CCC_sales@dell.com

Dell.com