



## Wyse 7030 zero client

High performance zero client  
purpose-built for VMware



### Meet the Wyse 7030 zero client for VMware.

For virtual desktop environments, the Wyse 7030 PCoIP zero client for VMware delivers workstation-level performance. Its dedicated hardware PCoIP engine delivers the highest level of display performance available for advanced applications, including CAD, 3D solids modeling, video editing and more.

Extremely compact and energy efficient, the 7030 PCoIP zero client is a fully functional VMware View end point that delivers a true PC-like experience with support for up to 4 displays. The 7030 offers the full benefits of an efficient and secure centralized computing environment, like multiple display support, multimedia playback, HD audio and four USB peripheral ports.

### Advanced performance. Higher quality.

The Wyse 7030 PCoIP zero client allows you to centrally manage your virtual desktops in a data center while still providing rich multimedia, high-resolution 3D graphics, HD media, and full USB peripheral interoperability locally over a LAN or remotely over a WAN. Optimized compression algorithms operate in real-time to achieve the best possible image quality for the available network bandwidth.

With Wyse thin clients, customers get a complete services portfolio including Deployment Services, ProSupport and Accidental Damage service, giving Dell business partners end-to-end support throughout the product lifecycle.

### Cool, simple performance

The 7030 PCoIP zero client for VMware draws under 15 watts of power, creating cooler, quieter working environments. Wyse zero clients for VMware receive and decode signals from the PCoIP host to create standard PC interfaces for the display, USB peripherals and audio.



## Specifications

## Dell Wyse 7030 zero client for VMware

|   |  |
|---|--|
| <b>Processor</b>                                | Teradici TERA2140 PCoIP  |
| <b>Memory</b>                                   | 32MB Flash / 512MB RAM DDR3  |
| <b>Power</b>                                    | Worldwide auto-sensing 100–240 VAC, 50/60Hz. power supply.<br>Multifunction power button LED   |
| <b>Power consumption</b>                        | Less than 15 watts   |
| <b>Security</b>                                 | Built-in Kensington security slot (cable sold separately)  |
| <b>Certifications<br/>(Based on US ratings)</b> | VMware Ready, PCoIP Connected  |
| <b>I/O peripheral support</b>                   | Four DisplayPort connectors<br>Four External USB 2.0 ports (2 front, 2 back)   |
| <b>Networking</b>                               | 10/100/1000 Base-T Gigabit Ethernet<br>Optional Fiber SFP Module Ready (Mutually Exclusive with RJ45) – available in the U.S. only   |
| <b>Display</b>                                  | VESA monitor support with Display Data Control (DDC)<br>for automatic setting of resolution and refresh rate<br>One display 2560 x 1600@60Hz, Color Depth: 8, 15, 16 or 24bpp<br>Two displays 2560 x 1600@60Hz, Color Depth: 8, 15, 16 or 24bpp<br>Four displays 1920 x 1200@60Hz, Color Depth: 8, 15, 16 or 24bpp |
| <b>Audio</b>                                    | Audio In 1/8-inch mini jack, 8-bit microphone<br>Output: 1/8-inch mini jack, full 16-bit stereo, 48KHz sample rate<br>One Line out / speaker 1/8-inch mini jack  |
| <b>Dimensions</b>                               | Height x Width x Depth<br>177 mm x 46 mm x 130 mm (6.97 in x 1.81 in x 5.12 in)<br>Weight 0.765kg (1.67lb)   |
| <b>Mountings</b>                                | Vertical feet  |
| <b>Temperature range</b>                        | Vertical position, power button up 10° to 40° C (50° to 104° F)<br>Storage -10° to 60° C (14° to 140° F)   |
| <b>Humidity</b>                                 | Condensing 20% to 80%<br>Non-condensing 10% to 95%   |
| <b>Keyboard and mouse</b>                       | Enhanced USB keyboard with Windows Keys (104 keys) - sold separately (availability varies by region).<br>USB optical mouse is included.  |
| <b>Warranty</b>                                 | 3-year limited hardware warranty   |
| <b>Support and deployment</b>                   | Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service.   |

Learn more: Visit [www.dell.com/wyse](http://www.dell.com/wyse)

Dell Inc.  
One Dell Way  
Round Rock, TX 78664

Visit our website at:  
[www.dell.com/wyse](http://www.dell.com/wyse)

Ask a Dell expert:  
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales  
1-800-438-9973  
[CCC\\_sales@dell.com](mailto:CCC_sales@dell.com)

Dell.com