



## Wyse 7040 thin client

Certified security for high-end computing

### The most powerful thin client from Dell

The Wyse 7040 is a high-powered, ultra-secure thin client. Equipped with 6<sup>th</sup> generation Intel i5/i7 processors, it delivers extremely high graphical display performance for seamless access to the most demanding applications. The Wyse 7040 is compatible with both data center hosted and client-side virtual desktop environments, including SecureView virtual desktop technology

### Ultra-secure

The Wyse 7040 is compliant with all relevant U.S. Federal security certifications including OPAL compliant hard-drive options, VPAT/Section 508, NIST BIOS, Energy-Star and EPEAT. Wyse enhanced Windows Embedded Standard 7P OS provides additional security features such as BitLocker.

### Highly Configurable

The Wyse 7040 offers a high level of connectivity including dual NIC, 6 x USB3.0 ports and an optional second network port, with either copper or fiber SFP interface. USB and wired network interfaces can be configured at a highly granular level, allowing individual customer requirements to be met.

### Easy Management

The Wyse 7040 devices are highly manageable through vPRO features and Wyse Device Manager(WDM), Microsoft System Center Configuration Manager(SCCM) and Dell Command Configure (DCC). Support by existing Dell best-in-class management tools such as WDM and DCC means that IT has access to rich management functionality for the Wyse 7040, including OS and BIOS imaging and BIOS configuration and password changes.

## Specifications

## Dell Wyse 7040 thin client

<b>Operating system</b>	Windows Embedded Standard 7P (Windows 10 IoT Enterprise Ready)
<b>CPU</b>	6th Generation Intel® Core™ i5 - 6500TE processor, 6th Generation Intel® Core™ i7-6700TE processor
<b>Memory</b>	4GB, 8GB, or 16GB RAM DDR4
<b>Storage</b>	128GB (Flash Media) / 256GB (Flash Media)
<b>I/O peripheral support</b>	6 x USB 3.0 ports, Display Port, HDMI Port, Ethernet, SFP (Fiber or Copper)
<b>Networking</b>	100Mb/1Gb Ethernet, 100Mb / 1Gb SFP (Copper or Fiber SFP Module)
<b>Resolution</b>	1 monitor at 4K (3840 * 2160) resolution 3 monitors at 2560 * 1600 resolution
<b>Audio</b>	Composite audio jack: 1/8-inch mini, 16-bit stereo / Internal mono speaker, audio out jack
<b>Dimensions</b>	Height: 7.16 in ( 182mm) x 7.01 in (178.2mm) x 1.41 in (36mm)
<b>Weight</b>	3.12lbs (1.41 kg)
<b>Mountings</b>	Optional VESA mounting bracket for mounting to flat surfaces, such as walls
<b>Security</b>	Trusted Platform Module (TPM) 1.2, VPAT / Section 508 certified, NIST BIOS, Kensington Lock, OPAL Compliant hard-drive options
<b>Power</b>	Worldwide auto-sensing 100-240 VAC, 50/60 Hz 65W, 19V DC Energy Star V.5.2 Phase V external and EuP compliant power adapter
<b>Temperature range</b>	Operating, vertical position: 41° to 95° F (5° to 35° C)
<b>Humidity</b>	20% to 80% condensing. 10% to 95% non-condensing
<b>Warranty</b>	Three-year limited hardware warranty with ProSupport (optional)
<b>Support and deployment</b>	Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service.

Learn more: Visit [www.dell.com/wyse](http://www.dell.com/wyse)

Dell Inc.  
One Dell Way  
Round Rock, TX 78664

Visit our website at:  
[www.dell.com/wyse](http://www.dell.com/wyse)

Ask a Dell expert:  
<https://marketing.dell.com/t2d-wyse>

Dell Cloud Client-Computing Sales  
1-800-438-9973  
[CCC\\_sales@dell.com](mailto:CCC_sales@dell.com)

Dell.com